



Product Technical Specification Sheet

Product Name: PROMELT Magic Minus Zero

Physical Characteristics:

No.	Properties	Test Method	Typical Values	Specification	
				min	max
1	Appearance	-	Brown	-	-
2	pH, deicer 1+4	ASTM D-1293	4.0	3.0	6.0
3	Specific Gravity (15°C 60°F)	ASTM D-1429	1.300	1.290	1.310
4	Weight (lbs/gal)	ASTM D-1429	10.85	10.76	10.93
5	Freeze Point Temperature	PNS	-45°C -49°F	-	-
6	% Freezer Settable Solids	PNS	<1.0	0.0	1.0
7	% Solids Passing #10 Sieve	PNS	>99.0	99.0	100.0
8	Total Dissolved Solids	-	38.4	37.4	45.4
9	Corrosion % effectiveness	NACE PNS	9.8	-	<30.0

Chemical Characteristics:

No.	Properties	Test Method	Typical Values	Specification	
				min	Max
10	% Magnesium Chloride	PNS	22.4	21.4	23.4
11	% Sodium Chloride	PNS	-	0.0	1.0
12	% Calcium Chloride	PNS	-	0.0	1.0
13	% Potassium Chloride	PNS	-	0.0	1.0
14	Arsenic (ppm)	EPA 200.7	<1.0	0.0	5.0
15	Barium (ppm)	EPA 200.7	<0.5	0.0	100.0
16	Cadmium (ppm)	EPA 200.7	<0.05	0.0	0.2
17	Chromium (ppm)	EPA 200.7	<0.5	0.0	1.0
18	Copper (ppm)	EPA 200.7	1.3	0.0	4.0
19	Cyanide (ppm)	EPA 335.4	<0.05	0.0	0.2
20	Lead (ppm)	EPA 200.7	<0.5	0.0	1.0
21	Mercury (ppm)	EPA 245.1	<0.02	0.0	0.05
22	Selenium (ppm)	EPA 200.7	<1.0	0.0	5.0
23	Zinc (ppm)	EPA 200.7	<0.1	0.0	10.0
24	Phosphorus (ppm)	EPA 365.4	15.9	0.0	2500.0

Version 2.0 | Page 1 of 1

ProMelt Magic Minus Zero
 Effective Date: January 2015
 www.innovativecompany.com

78 Orchard Road
 Ajax, Ontario L1S 6L1
 1-800-387-5777

454 River Road
 Glenmont, NY 12077
 1-800-257-5808